



POSITIVE OUTPUT WHEN THE LOAD IS APPLIED TO THE TOOL SIDE PER COORDINATE SYSTEM AS SHOWN

THE OUTPUTS ARE NOT STRUCTURALLY DECOUPLED
A 6X6 DECOUPLED MATRIX IS PROVIDED TO OBTAIN EACH COMPONENT

	F_x	F_y	F_z	M_x	M_y	M_z
CAPACITY (N/Nm)	900	900	1800	100	100	100
OUTPUT (mV/V)	COUPLED					
BRIDGE RES. (Ω)	350	350	350	350	350	350

SPECIFICATIONS	
EXCITATION MAX. (V)	7.5±0.5
OVERLOAD CAPACITY (%F.S.)	500
FREE AIR RESONANT FREQ. (HZ.)	4500
CROSSTALK (%F.S.)	2.5
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +100
COMPENSATED TEMP. RANGE (°C)	10 TO 70
MASS (KG)	0.24

WIRING CODE			
FUNCTION	COLOR	FUNCTION	COLOR
+VIN(+7V)	RED	CANL	WHITE
GND	BLACK	TX-RS232	ORANGE
CANH	GREEN	RX-RS232	YELLOW

SUNRISE INSTRUMENTS
www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL, COUPLED
D60MM F900N, W/DAS & CAN BUS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M3714B4	REV. A
--	---------	-----------