


WIRING CODE		
NO.	FUNCTION	COLOR
1.	22~50V(DC)	ORANGE
2.	GND	BLACK
3.	CAN_H	YELLOW
4.	CAN_L	GREEN
5.	RS232_TX	BROWN
6.	RS232_RX	GRAY

	Fx	Fy	Fz	Mx	My	Mz
CAPACITY (N/Nm)	300.0	300.0	300.0	30.0	30.0	30.0

SPECIFICATIONS	
POWER SUPPLY (V)	22~50V(DC)
OVERLOAD CAPACITY (%F.S.)	200
CROSSTALK (%F.S.)	2.5
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +90
COMPENSATED TEMP. RANGE (°C)	10 TO 70
IP PROTECTION	IP60
MASS (KG) NOT INCLUDING CABLE	0.185

SUNRISE INSTRUMENTS

www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
D50MM F300N, CAN,DC DC CONVERTER

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	C050J300L	REV. 0.1