



Sensor Cable Connector Definition

	Connector Model	Pin #	Function	Note
Power Input	DF62B-2EP-2.2C	1	GND	
		2	VBAT	
EtherCAT IN	DF62B-4EP-2.2C	4	RXIN	
		3	RXIP	
		2	TXIN	
		1	TXIP	
Power Output	XT30U-F	1	GND	
		2	VBAT	
EtherCAT OUT	GHR-05V-S	5	RXIN	
		4	RXIP	
		3	TXIN	
		2	TXIP	
		1	GND	

	Fx	Fy	Fz	Mx	My	Mz
CAPACITY (N/Nm)	300	300	300	30	30	30
OVERLOAD CAPACITY (N/Nm)	900	900	900	90	90	90

SPECIFICATIONS

EXCITATION (VDC)	48 V
CROSSTALK (%F.S.)	2
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
COMPREHENSIVE ACCURACY (%F.S.)	2.0
OPERATING TEMP. RANGE (°C)	-40 TO +90
COMPENSATED TEMP. RANGE (°C)	-10 TO 80
MASS (KG)	0.33

SUNRISE INSTRUMENTS

www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
D60MM F300N, ETHERCAT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MM

C060D300F

REV.
A