


SPECIFICATIONS

POWER SUPPLY (CUSTOMZABLE)		24±1VDC (TYP)
POWER CONSUMPTION (W)		3
INSULATION RESISTANCE		≥5000MΩ
SAMPLING RATE (Hz) MAX		2000
CROSSTALK (%F.S.)		2
NON-LINEARITY (%F.S.)		0.5
HYSTERESIS (%F.S.)		0.5
OPERATING TEMP. RANGE (°C)		-40 TO +100
COMPENSATED TEMP. RANGE (°C)		10 TO 70
CAPACITY	Fx=Fy=Fz	250N
	Mx=My=Mz	25Nm
OVERLOAD CAPACITY (%F.S.)		300
MATERIAL		AL ALLOY
IP PROTECION		IP60
MASS (KG) NOT INCLUDING ADAPTOR		0.27

M8 CONNECTOR PIN ASSIGNMENT

PIN #	FUNCTION	PIN #	FUNCTION
1 RED	RS485+	5 BROWN	+24V
2 BLACK	RS485-	6 WHITE	NA
3 ORANGE	RX	7 GREEN	NA
4 YELLOW	TX	8 BLUE	GND

LED STATUS	SENSOR STATUS
OFF	POWER OFF
FLIKER	WORK PROPERLY
ON	ABNORMAL

PEAK-TO-PEAK NOISE = 6.6 X RMS NOISE (EFFECTIVE RESOLUTION)
NOISE IS MEASURED AT SAMPLING RATE 200HZ

PEAK-TO-PEAK NOISE	0.237N	0.237N	0.134N	0.0048Nm	0.0048Nm	0.0083Nm
EFFECTIVE RESOLUTION	0.036N	0.036N	0.02N	0.0007Nm	0.0007Nm	0.0013Nm

SUNRISE INSTRUMENTS

www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
COMPATIABLE WITH ELITE ROBOTS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	C075A250K	REV. 0.1