



M8 CONNECTOR PIN ASSIGNMENT	
PIN #	FUNCTION
1 BROWN	24±1V(DC)
2 WHITE	RS485A
3 BLUE	RS485B
4 BLACK	GND

LED STATUS	SENSOR STATUS
OFF	POWER OFF
FLIKER	WORK PROPERLY
ON	ABNORMAL

	Fx	Fy	Fz	Mx	My	Mz
<b>CAPACITY (N/Nm)</b>	300N	300N	300N	30Nm	30Nm	30Nm
<b>OVERLOAD CAPACITY</b>	900N	900N	900N	90Nm	90Nm	90Nm

SPECIFICATIONS	
POWER SUPPLY	24±1V(DC)
CROSSTALK (%F.S.)	2
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +100
COMPENSATED TEMP. RANGE (°C)	10 TO 70
MASS (KG) NOT INCLUDING ADAPTOR	0.27

**SUNRISE INSTRUMENTS**  
[www.srisensor.com](http://www.srisensor.com)

SIX AXIS CIRCULAR LOAD CELL  
 D75MM, DIGITAL(RS485) OUTPUT  
 COMPATIBLE WITH AUBO

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	C075A300A	REV. 0.1
--	-----------	-------------