


CABLE #1	
COLOR	FUNCTION
ORANGE	24±IV(DC)
BLACK	GND
GRAY	RX
BROWN	TX

M8 CONNECTOR PIN ASSIGNMENT					
PIN#	FUNCTION	COLOR	PIN#	FUNCTION	COLOR
1	24±IV	ORANGE	5	RXP	YELLOW
2	GND	BLACK	6	RXN	GREEN
3	TXP	BLUE	7	RX	GRAY
4	TXN	WHITE	8	TX	BROWN

LED STATUS	SENSOR STATUS
OFF	POWER OFF
FLIKER	WORK PROPERLY
ON	ABNORMAL

SPECIFICATIONS		
POWER SUPPLY (CUSTOMZABLE)		24±IVDC (TYP)
POWER CONSUMPTION (W)		3
INSULATION RESISTANCE		≥5000MΩ
SAMPLING RATE (Hz) MAX		2000
CROSSTALK (%F.S.)		2
NON-LINEARITY (%F.S.)		0.5
HYSTERESIS (%F.S.)		0.5
OPERATING TEMP. RANGE (°C)		-40 TO +100
COMPENSATED TEMP. RANGE (°C)		10 TO 70
CAPACITY	Fx=Fy=Fz	200N
	Mx=My=Mz	20Nm
OVERLOAD CAPACITY (%F.S.)		300
MATERIAL		AL ALLOY
MASS (KG) NOT INCLUDING ADAPTOR		0.25

PEAK-TO-PEAK NOISE = 6.6 X RMS NOISE (EFFECTIVE RESOLUTION)
NOISE IS MEASURED AT SAMPLING RATE 200HZ

PEAK-TO-PEAK NOISE	0.2N	0.2N	0.1N	0.004Nm	0.004Nm	0.008Nm
EFFECTIVE RESOLUTION	0.03N	0.03N	0.015N	0.0006Nm	0.0006Nm	0.0012Nm

SUNRISE INSTRUMENTS

www.srisensor.com

SIX AXIS CIRCULAR LOAD CELL
D75MM, ETHERNET TCP/IP OUTPUT, IP64

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	C075E200C	REV. A