



POSITIVE OUTPUT WHEN THE LOAD IS APPLIED TO THE TOOL SIDE  
 PER COORDINATE SYSTEM AS SHOWN  
 THE OUTPUTS ARE NOT STRUCTURALLY DECOUPLED  
 A 6X6 DECOUPLED MATRIX IS PROVIDED TO OBTAIN EACH COMPONENT

	Fx	Fy	Fz	Mx	My	Mz
<b>CAPACITY (N/Nm)</b>	100	100	100	5	5	5
<b>OUTPUT (mV/V)</b>	COUPLED					
<b>BRIDGE RES. (Ω)</b>	350	350	350	350	350	350

SPECIFICATIONS	
EXCITATION MAX. (V)	5
OVERLOAD CAPACITY (%F.S.)	300
FREE AIR RESONANT FREQ. (HZ.)	1500
CROSSTALK (%F.S.)	2.5
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +100
COMPENSATED TEMP. RANGE (°C)	10 TO 70
MASS (KG)	0.18

WIRING CODE - TWISTED PAIR						
FUNC	CHN1	CHN2	CHN3	CHN4	CHN5	CHN6
+SIG	WHITE (BROWN)	ORG (BROWN)	BLUE (BROWN)	YEL (BROWN)	RED (BROWN)	WHITE (BLACK)
-SIG	BROWN (WHITE)	BROWN (ORG)	BROWN (BLUE)	BROWN (YEL)	BROWN (RED)	BLACK (WHITE)
+EXC	ORG (BLACK)	BLACK (ORG)	BLUE (BLACK)	BLACK (BLUE)	RED (BLACK)	BLACK (RED)
-EXC	YELLOW (BLACK)			BLACK (YELLOW)		
"YEL"="YELLOW", "ORG"="ORANGE", "WHITE (BROWN)" = WHITE CABLE IN WHITE/BROWN PAIR						

**SUNRISE INSTRUMENTS**  
[www.srisensor.com](http://www.srisensor.com)

SIX AXIS CIRCULAR LOAD CELL, COUPLED  
 D63MM F100N, ANALOG OUTPUT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M3635A	REV. A
--	--------	-----------