





	F _x	F _y	F _z	M _x	M _y	M _z
CAPACITY (N/Nm)	5000	5000	8000	500	500	300
OUTPUT (Communication)	CAN OR RS232					
RESOLUTION (N/Nm)	0.2424	0.2424	1.4697	0.0197	0.0197	0.0068

WIRING CODE		
NO.	FUNCTION	COLOR
1.	+24	RED
2.	GND	BLACK
3.	CAN_H	WHITE&BLUE
4.	CAN_L	WHITE
5.	RS232_TX	BLUE
6.	RS232_RX	YELLOW

SPECIFICATIONS	
POWER SUPPLY (V)	+24±1V
OVERLOAD CAPACITY (%F.S.)	200
CROSSTALK (%F.S.)	2.5
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
OPERATING TEMP. RANGE (°C)	-40 TO +100
COMPENSATED TEMP. RANGE (°C)	10 TO 70
MASS (KG) NOT INCLUDING ADAPTOR	0.35
SUNRISE INSTRUMENTS www.srisensor.com	
SIX AXIS LOAD CELL D65MM F8000N, CAN OR RS232	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM	M3636S5E3 REV. B