



THE OUTPUT IS POSITIVE WHEN THE LOAD IS APPLIED TO THE TOOL SIDE PER COORDINATE AS SHOWN. A 6X6 MATRIX IS PROVIDED FOR DECOUPLING

	Fx	Fy	Fz	Mx	My	Mz
<b>CAPACITY (N/Nm)</b>	520N	520N	520N	56Nm	56Nm	56Nm
<b>OUTPUT @ F.S.(V)</b>	5	5	5	5	5	5

#### LEMO PIN ASSIGNMENT

PIN #	FUNCTION	PIN #	FUNCTION	PIN #	FUNCTION
1 & 2	GND	7	+CHN2	12	-CHN4
3	+PWR	8	-CHN2	13	+CHN5
4		9	+CHN3	14	-CHN5
5	+CHN1	10	-CHN3	15	+CHN6
6	-CHN1	11	+CHN4	16	-CHN6

#### SPECIFICATIONS

POWER SUPPLY (V)	12-24V
OVERLOAD CAPACITY (%F.S.)	1000
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	0.5
CROSSTALK (%F.S.)	2.0
RESOLUTION (WITH M8125, 16 BIT)	1/5000
RESONANT FREQ. (FX,FY,MZ) (HZ.)	1250
RESONANT FREQ. (FZ,MX,MY) (HZ.)	2220
OPERATING TEMP. RANGE (°C)	-40 TO +100
MASS (KG)	0.69

**SUNRISE INSTRUMENTS**

[www.srisensor.com](http://www.srisensor.com)

SIX AXIS LOADCELL WITH OL STOPS & AMP  
D100MM F260N, IP60

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN MM

M3816E

REV.  
A